

- Home
- Environmental Overview
- Residential
- Commercial
- Features and benefits
- Indoor environment quality
- SBR Latex Underlays
- Recycled Textile
- Ignition Resistant
- Specifications
- Specifiers Application Guide
- Warranty
- General Recommendations
- Contact Airstep
- Tipping Competition

Home > Commercial > Specifications

Airstep Carpet Underlay Specifications - Commercial
Specification Summary - Double Bond Installations

PRODUCT	GRADE	WEIGHT g/m2	ROLL LENGTH metres	ROLL WIDTH metres	THICKNESS mm
Airstep Slab	****	1390 ± 50	10	1.83	4.7
Airstep Sensi Slab	****	1390 ± 50	10	1.83	4.7
Airstep Suporta Pad	*****	1300 ± 50	12	1.83	3.7
Airstep Aero Cushion	*****	2200 ± 80	6	1.83	7.0
Airstep Cushion Bond 6000	****	900 ± 50	25	1.83	6.0
Airstep Cushion Bond SC 6000	****	900 ± 50	25	1.83	6.0
Airstep Cushion Bond 7000	*****	1100± 50	25	1.83	7.0
Airstep Resist	*****	1390 ± 50	10	1.83	5.1

Specification Summary - Made To Order Products

PRODUCT	GRADE	WEIGHT g/m2	ROLL LENGTH metres	ROLL WIDTH metres	THICKNESS mm
Airstep Xtenda Slab	*****	1800 ± 50	8	1.83	6.0
Airstep Sensi Slab AM	****	1390 ± 50	10	1.83	4.7

Conventional Stretch-in Installations

PRODUCT	GRADE	WEIGHT g/m2	ROLL LENGTH Metres	ROLL WIDTH metres	THICKNESS mm
Airstep Black Comfort	**	1830 ± 55	15	1.22	7.5
Airstep Premium Gold	***	2360 ± 55	12	1.22	8.5
Airstep Platinum Supreme	****	2535 ± 55	12	1.22	9.5
Airstep Supreme Green	****	2450/55	12	1.22	9.0
Airstep Supa Blue	*****	3200 ± 55	9	1.22	9.5

Airstep Defiance	***	2115 ± 55	12	1.22	8.0
Airstep Prime	*****	3000 ± 75	9	1.22	7.6
Airstep Firecheck	*****	3000 ±75	9	1.22	7.6
Airstep Cushion Pad	***	1050 ± 50	25	1.83	9.0
Airstep Premier Pad	*****	1550 ± 55	25	1.83	14.5
Airstep Protecta Pad	****	1050 ± 50	25	1.83	9.0
Airstep Budget Pad	***	700 ± 50	25	1.83	7.5
Airstep Econo Pad	***	700 ± 50	25	1.83	7.5

**For a detailed specification sheet on individual products contact Bridgestone